

INDUSTRIAL

SERIES: GDNYLF / TL

BRACKET: **PRESSED STEEL**
 WHEEL: **NYLON**
 BEARING: **BALL BEARING**



MEDIUM / HEAVY

LEVELLING CASTOR




GDNYLF SWIVEL										
65GD4NYLF	65	43			120X120	98/93x 98/93	11	30	97	150
75GD4NYLF	75	45			120X120	98/93x 98/93	11	30	102	200




GDNYLF BOLT HOLE									
65GDBH13NYLF	65	43				13	30	94	150
75GDBH13NYLF	75	45				13	30	99	200



USE AND OPERATION



01
 When retracted, the foot pitches upward in the direction of motion and contacts the wheel on a point. This ensures ramp clearance, impact resistance and the foot will not be damaged by the rotating wheel.



02
 The foot is adjusted downward until it touches the floor. Over a few turns, the weight will be fully transferred from the castor to the extended foot.

TRUCK LOCK

Our Truck locks are designed to enable a quick, free and easy change between locked and free movement modes. This is restored by the quick release pedal and moderate force. Our Truck Locks are of pressed steel with a zinc-plated finish.



TL					
TL4	125	151	120x120	85/100x 85/100	11
TL6	170	210	120x120	85/100x 85/100	11