

INDUSTRIAL

SERIES: LVHT/G/BJG

BRACKET: **PRESSED STEEL**
 WHEEL: **HIGH TEMPERATURE RESISTANT**
 WHEELS 220 °C, 260 °C OR 280 °C
 BEARING: **PLAIN / BALL BEARING**



LIGHT / MEDIUM



LVHT/G SWIVEL										
100LV4HT 220	100	38		105x85	80x60	9	40	128		150
100LV4HTG 280	100	38		105x85	80x60	9	40	128		200



LVHT/G FIXED										
100LV8HT 220	100	38		105x85	80x60	9		128		150
100LV8HTG 280	100	38		105x85	80x60	9		128		200



LVHT/G BOLT HOLE										
100LVBH12HT 220	100	38					12.1	40	128	150
100LVBH12HTG 280	100	38					12.1	40	128	200



LVHTBJG SWIVEL										
80LV4HT 260	80	30		105x85	80x60	9	40	106		200
80LV4HTBJG 260	80	30		105x85	80x60	9	40	106		200
100LV4HT 260	100	32		105x85	80x60	9	40	128		220
100LV4HTBJG 260	100	32		105x85	80x60	9	40	128		220
125LV4HT 260	125	40		105x85	80x60	9	40	155		250
125LV4HTBJG 260	125	40		105x85	80x60	9	40	155		250



LVHTBJG FIXED										
80LV8HT 260	80	30		105x85	80x60	9		106		200
80LV8HTBJG 260	80	30		105x85	80x60	9		106		200
100LV8HT 260	100	32		105x85	80x60	9		128		220
100LV8HTBJG 260	100	32		105x85	80x60	9		128		220
125LV8HT 260	125	40		105x85	80x60	9		155		250
125LV8HTBJG 260	125	40		105x85	80x60	9		155		250



LVHTBJG BOLT HOLE										
80LVBH12HT 260	80	30					12.1	40	106	200
80LVBH12HTBJG 260	80	30					12.1	40	106	200
100LVBH12HT 260	100	32					12.1	40	128	220
100LVBH12HTBJG 260	100	32					12.1	40	128	220
125LVBH12HT 260	125	40					12.1	40	155	250
125LVBH12HTBJG 260	125	40					12.1	40	155	250

260°C CONSTANT (280°C SHORT PERIODS) (LVHTBJG ONLY)